



SUGAR STAINLESS STEEL TUBES

Standard range		Thickness			
		1,2 mm	1,5 mm	1,6 mm	2 mm
Diameter		18 bwg		16 bwg	14 bwg
30		○	○	○	
32		○	○	○	
33		○	○	○	
35	1"3/8	○	○	○	○
38,1	1"1/2	○	○	○	
41,3	1"5/8	○	○	○	
42,4		○	○	○	○
44,5	1"3/4	○	○	○	○
50,8	2"	○	○	○	○
101,6	4"		○	○	○

We are producing for more than 30 years of stainless steel tubes for the sugar industry.

Solutions adapted to your needs.

Production in ferritic and austenitic grades.

Classic tubes + Transtherm™ tubes.

Advice and after-sales service.

Reliability of your process.

Worldwide industrial references.

ASTM A268 for ferritic grades.

Dimensional tolerances

Diameter	Min $\pm 0,13$ mm ($\pm 0,05$ "')		
	Max $\pm 0,75$ %		
Thickness	± 10 %		
Length	L < 5 meters	5 < L < 10 meters	L > 10 meters
	L < 16,5'	16,6 < L < 33'	L > 33'
	-0 / +3 mm	-0 / +6 mm	-0 / +9 mm
Straightness	1 mm/m		
Max length	17 meters (55,8')		